

**Acrylic Primer Undercoat**

**Description**

Ezicover Acrylic Primer Undercoat is a premium quality, fast drying acrylic primer designed for use on treated absorbent timber, masonry and plaster surfaces. When used as a primer on timber, Ezicover Acrylic Primer Undercoat significantly reduces chances of tannin-stains from penetrating through to the finish coat. It may be top-coated with the Ezicover range of acrylic finishes, enamels as well as APCO Timbercare Low Sheen Acrylic and Ezicover Aquanamel. The use of this product as an undercoat also results in improved gloss levels of the finish coats due to its exceptional ability to seal surfaces.

**Features and Benefits**

- Easy application
- Exceptional sealing/penetrating properties
- Excellent coverage/hiding power
- Ideal for absorbent surfaces like timber, plaster and masonry
- Low splatter
- Low VOC
- Suitable for interior and exterior use

**Limitations and Precautions**

- Some surfaces may require the use of an oil based sealer or primer. E.g. very oily/sappy timbers or very aged previously painted surfaces. A test application should be done first to ensure proper adhesion and proper stain blocking properties.
- Do not apply when the surface temperature is below 10°C or above 35°C.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply if humidity is 85% or above.

**Technical Data**

|                             |  |
|-----------------------------|--|
| <b>Resin Type</b>           | Acrylic Emulsion   |
| <b>Colour</b>               | White  |
| <b>Gloss Level</b>          | na   |
| <b>Dry Times</b>            | Touch dry: 30 minutes<br>Minimum Re-coat: 2 hours<br>Cool temperatures, high film thickness or high humidity will require longer drying times. |
| <b>Theoretical Coverage</b> | 8 - 10 m <sup>2</sup> per litre  |
| <b>No. of coats</b>         | One. On tannin rich timbers, two coats may be required.  |
| <b>Flash Point</b>          | None   |
| <b>Thinner</b>              | Water  |
| <b>Theoretical VOC</b>      | 28 g/l   |

### Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface.

Fill cracks and imperfections with a suitable filler and spot prime.

Previously painted surfaces should be sanded to remove loose or flaking paint and to reduce the previous film to a flat finish.

### Application

Stir the contents thoroughly before and during use.

Apply a liberal coat then sand smooth before applying topcoats.

Apply by brush, roller or spray.

### For Best Results

- The use of good quality brushes and rollers is recommended.
- Allow a minimum of 2 hours prior to sanding and top-coating.
- Top coat with Ezicover DTS Acrylic for maximum exterior protection.
- Do not apply in direct sunlight.

**Health and Safety** (Please refer to Material Safety Data Sheet before using)

**Ezicover Acrylic Primer Undercoat** is non-flammable and non-hazardous.

**KEEP OUT OF REACH OF CHILDREN**

#### Product Number

EZIB101

V 1.3 - 06.15

Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.