

**Semi Gloss Acrylic**

**Description**

Ezicover Semi Gloss Acrylic is a premium, 100% acrylic finish. Suitable for interior and exterior use. Specifically formulated to give a very tough, durable, easy to clean finish. Suitable for walls in high traffic commercial and domestic areas.

**Features and Benefits**

- Easy application
- Easy cleaning. Most common stains can be removed with a damp cloth
- Excellent adhesion to primed and properly prepared painted surfaces
- Excellent coverage
- Ideal for high traffic interior areas and a variety of exterior surfaces
- Low splatter
- Low VOC
- Mould resistant

**Limitations and Precautions**

- Not recommended for bathrooms, kitchens or laundries.
- Avoid cleaning the paint surface in the first 4 – 6 weeks.
- Do not apply when the surface temperature is below 10°C or above 35°C.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply if humidity is 85% or above.
- Being thermoplastic, the film is sensitive towards alcohol and aromatic hydrocarbons.
- Always test cleaning solutions to make sure they will not damage the paint surface.
- Some insect treatments contain chemicals that can soften and stain painted surfaces.

**Technical Data**

|                             |                                                                                                                                                                     |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Resin Type</b>           | Pure Acrylic Emulsion                                                                                                                                               |
| <b>Colour</b>               | White and tint bases                                                                                                                                                |
| <b>Gloss Level</b>          | 20 - 30 @ 60°                                                                                                                                                       |
| <b>Dry Times</b>            | Touch dry: 30 minutes<br>Minimum Re-coat: 2 hours<br>Full cure: 7 days<br>Cool temperatures, high film thickness or high humidity will require longer drying times. |
| <b>Theoretical Coverage</b> | 10 - 12 m <sup>2</sup> per litre                                                                                                                                    |
| <b>No. of coats</b>         | Two                                                                                                                                                                 |
| <b>Flash Point</b>          | None                                                                                                                                                                |
| <b>Thinner</b>              | Water                                                                                                                                                               |
| <b>Theoretical VOC</b>      | 41 g/l                                                                                                                                                              |

### Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface.

Fill cracks and imperfections with a suitable filler and spot prime.

Previously painted surfaces should be sanded to remove loose or flaking paint and to reduce the previous film to a flat finish.

### Undercoat Requirements

*New Paper-faced Plasterboard:*

Ezicover Acrylic Sealer Undercoat or Ezicover Smooth-coat.

*New Woodwork, Plywood, Hardboard:*

Ezicover Acrylic Primer Undercoat or Ezicover Alkyd Primer Undercoat.

*Aged Plaster and Paper-faced Plasterboard, discoloured or very aged previous paint:*

Ezicover Pigmented Sealer.

### Application

Stir the contents thoroughly before and during use.

Apply two liberal coats of Ezicover Semi Gloss Acrylic.

Apply by brush, roller or spray.

### For Best Results

- The use of an 8 – 10mm nap roller is recommended.
- Allow a minimum of 2 hours prior to sanding and recoating.
- For best results, apply one coat of Ezicover Smooth-coat by spray application, then one coat of Ezicover Acrylic Sealer Undercoat.
- When painting over medium to dark colours, a tinted undercoat must be used for superior coverage.

**Health and Safety** (Please refer to Material Safety Data Sheet before using)

**Ezicover Semi Gloss Acrylic** is non-flammable and non-hazardous.

### KEEP OUT OF REACH OF CHILDREN

#### Product Numbers

|         |                   |
|---------|-------------------|
| EZIT130 | White             |
| EZIT135 | Mid Tone base     |
| EZIT133 | Ultra Deep Base   |
| EZIT134 | Extra Bright base |

V 1.3 - 06.15

Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.