

Technical Data Sheet
Product No: EZIB301S**APCO EZI-COVER**
Pigmented Sealer**Description:**

An alkyd based wallboard sealer for sealing level 3 based Gibraltar Board, fibre cement and interior timber surfaces. It is specifically designed for application by professional tradesmen and possesses controlled penetration giving a more uniform porosity to porous surfaces and does not raise the grain of paperfaced gibraltar board significantly. It has high opacity and very easy sanding properties.

Features and Benefits:

- Excellent adhesion Properties to porous surfaces
- Controlled penetration to give more uniform porosity
- Very easy sanding properties
- High hiding, usually one coat only required
- May be over coated with solvent or waterborne topcoats

Limitations:

Do not apply when ambient temperature is below 10°C.

Technical Data:

| | |
|-------------------------|---------------------------------|
| Resin Type: | Medium alkyd resin |
| Solvents: | White Spirit/Mineral Turps |
| Colour: | White |
| Density: | 1.20 Kgs/ Litre |
| Dry-Time: | 2-3 hr handle, 12 hr overcoat |
| Coverage: | 8 - 12 m ² per litre |
| Packaging sizes: | 4 and 10 litre |
| Flash Point: | 38°C – Flammable |
| Thinner: | White Spirit or Mineral Turps |

Surface Preparation:

Surface must be dry and thoroughly cleaned to remove all traces of dust, dirt, moss oil and grease, bird droppings etc. Areas of plaster stopping should be well sanded smooth with 280 grit sandpaper and dusted clean. If necessary remove all dust with a tack-rag.

Application:

Apply by brush, roller or airless spray. Do not thin for brushing or rolling, but add 5% mineral turps for airless spray. Apply one full coat, at the recommended coverage to the entire area. Allow at least 6 hours before sanding.

For Best Results:

- 1) Apply the product at the one time evenly to the entire area.
- 2) Do not thin for brushing or rolling.
- 3) Allow overnight prior to sanding with a flat block
- 4) Can be overcoated with solvent or waterborne systems.

Health and Safety: (Please refer to Material Safety Data Sheet before using)

Ezicover Pigmented Sealer is essentially **flammable – keep away from naked flame**, but non-toxic. Does not contain any added toxic heavy metals such as lead, mercury etc. Provide plenty of ventilation and avoid breathing vapours.

KEEP OUT OF REACH OF CHILDREN