

## Aquanamel

### Description

Ezicover Aquanamel is a professional quality, new generation 100% acrylic emulsion based paint. It has the hardness of an oil based enamel, with the convenience of fast dry, low odour and clean-up with water.

Available in Low Sheen, Semi Gloss & Gloss finishes.

### Features and Benefits

- Easy application
- Excellent adhesion to primed and properly prepared painted surfaces
- Extremely durable, hard wearing finish
- High cover formula
- Ideal for bathrooms, kitchens, laundries, doors and trims
- Low splatter
- Low VOC
- Mould resistant
- Suitable for interior and exterior use

### Limitations and Precautions

- Avoid exposure to excessive steam or moisture for the first 14 days.
- Do not apply when the surface temperature is below 10°C or above 35°C.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply if humidity is 85% or above.

### Technical Data

<b>Resin Type</b>	100% Acrylic Emulsion
<b>Colour</b>	White & tint bases
<b>Gloss Level</b>	Low Sheen: 8 - 12 @ 60° Semi Gloss: 20 - 30 @ 60° Gloss: > 40 @ 60°
<b>Dry Times</b>	Touch dry: 30 minutes Minimum Re-coat: 2 hours Full cure: 7 days Cool temperatures, high film thickness or high humidity will require longer drying times.
<b>Theoretical Coverage</b>	10 - 12 m <sup>2</sup> per litre
<b>No. of coats</b>	Two
<b>Flash Point</b>	None
<b>Thinner</b>	Water
<b>Theoretical VOC</b>	Low Sheen: 45 g/l Semi Gloss: 47 g/l Gloss: 57 g/l

### Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface.

Fill cracks and imperfections with a suitable filler and spot prime.

Previously painted surfaces should be sanded to remove loose or flaking paint and to reduce the previous film to a flat finish.

### Undercoat Requirements

*New Paper-faced Plasterboard:*

Ezicover Acrylic Sealer Undercoat

*New Woodwork, Plywood, Hardboard:*

Ezicover Acrylic Primer Undercoat or Ezicover All 'n One Primer or Ezicover Alkyd Primer Undercoat.

*Aged Plaster and Paper-faced Plasterboard, discoloured or very aged previous paint:*

Ezicover Pigmented Sealer.

### Application

Stir the contents thoroughly before and during use.

Apply two liberal coats with light sanding between coats.

Apply by brush, roller or spray.

Avoid over-brushing or rolling back over paint that has been recently applied.

### For Best Results

- Apply one coat of Ezicover All 'n One Primer over the appropriate preparatory undercoat.
- The use of good quality brushes and rollers is recommended.
- Allow a minimum of 2 hours prior to sanding and recoating.
- When painting over medium to dark colours, a tinted undercoat must be used for superior coverage.

**Health and Safety** (Please refer to Material Safety Data Sheet before using)

**Ezicover Aquanamel** is non-flammable and non-hazardous.

### KEEP OUT OF REACH OF CHILDREN

#### Product Numbers

EZIT220 Low Sheen White

EZIT230 Semi Gloss White

EZIT241 Gloss White

EZIT225 Low Sheen Mid Tone base

EZIT235 Semi Gloss Mid Tone

EZIT245 Gloss Mid Tone

EZIT223 Low Sheen Ultra Deep base

EZIT233 Semi Gloss Ultra Deep

EZIT243 Gloss Ultra Deep

EZIT224 Low Sheen Extra Bright base

EZIT234 Semi Gloss Extra Bright base

EZIT244 Gloss Extra Bright

V 1.3 - 06.15 Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.