

ezi•cover

Acrylic Ceiling Finish

Dead Flat

Description:

Ezicover Acrylic Ceiling Finish is a premium Acrylic finish. Specifically formulated to give a smooth, ultra flat finish for interior ceilings.

Features and Benefits:

- Contains dry film mould inhibitors
- Excellent flow and application properties
- Smooth, ultra flat finish that hides imperfections
- Excellent adhesion to primed and correctly prepared old paintwork
- High opacity

Limitations:

Do not apply when ambient temperature is below 10°C or surface temperature is above 40°C.

Do not apply to a bare surface.

Not recommended for wet areas.

Flat finishes can develop shiny spots when cleaned vigorously or with the use of abrasives.

Technical Data:

Resin Type:	Acrylic Emulsion
Pigmentation:	Titanium dioxide and inert extenders
Solvents:	Water
Colour:	White
Gloss Level:	Dead Flat
Density:	1.52 Kgs/ Litre
Dry-Time:	30 mins Touch, 2 hour overcoat
Coverage:	12 - 16 m ² per litre
No. of coats:	One to Two
Packaging sizes:	4 and 10 litre
Flash Point:	None
Thinner:	Water

Surface Preparation:

Remove all unsound paint, surface grease and oil, dirt etc. and apply a coat of Ezicover Acrylic Sealer Undercoat or Ezicover Pigmented Sealer. Sand smooth all stopped areas of new paper-faced plasterboard and remove dust. All holes & defects should be primed, filled & sealed with either Ezicover Acrylic Sealer Undercoat or Ezicover Pigmented Sealer.

Application:

Apply by brush, roller or airless spray. Apply One to Two liberal coats, at the recommended coverage, to a properly prepared surface. Allow at least 2 hours dry time between coats. To keep brushes and rollers working freely, rinse occasionally with clean water.

For Best Results:

- 1) Apply liberal coats by brush, roller or spray unthinned, maintaining a wet edge.
- 2) For ceilings that are discoloured or if the previous paint is very old, first use Ezicover Pigmented Sealer then lightly sand the entire surface.

Health and Safety: (Please refer to Material Safety Data Sheet before using)

Ezicover Acrylic Ceiling Finish is essentially non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN



0800 BUY APCO
Ph. 09) 2733 041
Fax. 09) 2733 045

PO Box 58849
Botany
Manukau 2163