

ezi•cover

Galvanised Iron Primer

Description:

A Premium Quality Galvanised Iron Primer, designed for direct application to interior or exterior galvanising, new or weathered galvanised Sheet Steel and Aluminium.

Features and Benefits:

- Excellent adhesion Properties
- Latest Acrylic Anti-Corrosive technology
- Very low toxicity.
- Allows immediate painting of Sheet Galvanising Roofs
– no weathering required or recommended.
- Can be over-coated with most Acrylic topcoats.

Limitations:

Do not apply when ambient temperature is below 10°C or when the roof is hot to touch.

Technical Data:

Resin Type:	Styrene/Acrylic Emulsion
Solvents:	Water
Colour:	Light Grey
Density:	1.36 Kgs/ Litre
Dry-Time:	30 mins Touch, 2 hour overcoat.
Coverage:	10 - 12 m ² per litre.
Packaging sizes:	10 litre
Flash Point:	None
Thinner:	Water

Surface Preparation:

Surface must be thoroughly cleaned to remove all traces of dust, dirt, moss oil and grease, bird droppings etc. All areas of brown rust **MUST** be treated either by removing with rust remover or neutralising with a rust converter eg. Levene Rustcon. Very new galvanised sheet steel must be degreased then rinsed with clean water and allowed to dry. Moss and Mould can be removed with APCO BioWash.

Application:

Apply one liberal coat at the recommended coverage, to the clean metal surface by Brush, Roller or Spray. To keep brushes and rollers working freely rinse occasionally with clean water.

For Best Results:

- 1) Apply the product by Brush to ensure maximum contact with the metal surface.
- 2) With repaints, spot prime with **ezicover Galvanised Iron Primer**, followed by one full coat of the topcoat.
- 3) Can be over-coated with most acrylic systems.

Health and Safety: (Please refer to Material Safety Data Sheet before using)

ezicover Galvanised Iron Primer is essentially non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN



0800 BUY APCO
Ph. 09) 2733 041
Fax. 09) 2733 045

PO Box 58849
Botany
Manukau 2163