



ezi•cover

Satin Roof Acrylic

Description:

Ezicover Satin Roof Acrylic is a high quality, 100% Acrylic paint for the protection of new and previously painted roofs. This product offers a non-toxic film when fully dried. Provides durability & protection against rain and other elements. Excellent adhesion to properly prepared Galvanised Iron, Concrete & Clay tiles.

Features and Benefits:

- Excellent Durability. Tough Satin Finish
- Excellent Opacity
- Suitable for the collection of drinking water - disconnect down pipes before painting and allow a heavy shower to wash the surface before reconnecting.

Limitations:

- Do not apply when ambient temperature is below 10°C. or surface temperature is above 45°C.

Technical Data:

Resin Type:	100% Acrylic polymer
Pigmentation:	Titanium Dioxide and inert extenders
Solvents:	Water
Colour:	Refer to the Colour Chart
Gloss Level:	Satin
Dry-Time:	30 mins Touch, 4 hour between overcoat
Coverage:	12 – 14m ² per litre: depending on the porosity of the substrate
No. of coats:	Two
Packaging sizes:	10 Litre
Flash Point:	None
Thinner:	Water

Technical Data Sheet:



Surface Preparation:

Remove all unsound paint, surface grease and oil, dirt etc. Treat mould affected areas with APCO Biowash Moss & Mould Remover & allow to dry. Rusted Iron requires the use of appropriate rust removers/converters.

Check the adhesion of any previous paint before repainting.

Application:

Galvanised Iron

Unpainted: Apply one coat of Ezicover Galvanised Iron Primer. Allow to dry fully then apply one coat of Ezicover Satin Roof Acrylic. Apply the second coat after a minimum of 2 hours.

For coastal areas & added protection, a third coat may also be applied.

Previously Painted: Spot prime any bare areas of Iron with Ezicover Galvanised Iron Primer. Allow to dry fully, then apply 2 coats of Ezicover Satin Roof Acrylic with a minimum of 2 hours in between coats. During times of cool temperatures & high humidity, longer drying times may be required.

Concrete/Clay Tile

Unpainted: Apply the first coat of Ezicover Satin Roof Acrylic thinned with a minimum of 20% water. Apply the second coat after a minimum of 2 hours.

For coastal areas & added protection, a third coat may also be applied.

Previously Painted: Spot prime any bare areas with Ezicover Satin Roof Acrylic thinned with a minimum of 20% water. Allow to dry fully, then apply 2 coats of Ezicover Satin Roof Acrylic with a minimum of 2 hours between coats. During times of cool temperatures & high humidity, longer drying times may be required.

Ezicover Satin Roof Acrylic can be applied by Airless Spray, Brush or Roller.

For Best Results:

- 1) Allow at least 2 hours between coats.
- 2) Do not spread the paint beyond 14m² on Galvanised Iron
- 3) Do not apply in direct sunshine.
- 4) For coastal areas a third coat will provide extra protection.

Health and Safety: (Please refer to Material Safety Data Sheet before using)

Ezicover Satin Roof Acrylic is essentially non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN



0800 BUY APCO
Ph. 09) 2733 041
Fax. 09) 2733 045

PO Box 58849
Botany
Manukau 2163