

PRODUCT DATA SHEET

PDS No: 1006

Product Details

Product Code: EZIB101P
Product Name: Ezicover All 'n One Primer
Other Name(s): Not Applicable

Description

Ezicover All 'n One Primer is a high performance, water-based preparation product. It has outstanding hiding, filling and sanding properties. Specifically formulated as a smooth surface sealer.

Uses- Suitable for new paper-faced plasterboard, MDF(custom wood) & interior timber.

Features and Benefits

- Excellent adhesion to properly prepared smooth surfaces like glossy alkyds and varnishes
- Exceptional coverage/hiding power
- Low VOC
- Contains Mould inhibitors
- Suitable for interior and exterior use
- When used as an undercoat, **Ezicover All 'n One Primer** provides a smooth, even surface for topcoats to achieve maximum coverage and gloss level.

Limitations and Precautions

- Not recommended for fibrous plaster or very porous surfaces.
- Full adhesion and hardness will take a minimum of 7 days
- The surface must be de-greased prior to application
- Do not apply to timber that is showing signs of deterioration
- Check the weather forecast. **Do Not** apply if rain, heavy dew or a sudden drop in temperature is likely during application or during the first 12 hours after application
- **Do Not** apply if humidity is 85% or above

PRODUCT DATA SHEET

PDS No: 1006

Physical Properties

| | |
|--|--|
| Resin Type | Acrylic Emulsion |
| Pigmentation | Titanium Dioxide and Inert Extenders |
| Colour | White (can be custom tinted) |
| Gloss at 60° head | Not applicable |
| Specific Gravity(Kg/Ltr) | 1.29-1.39 |
| Coverage (m²/Ltr) | 10-12 |
| No. of coats | One (Two for stained surfaces) |
| Dry Times(at 20°C and 60%RH)* | 30 min |
| *(cooler temperatures, higher film thickness and higher humidity can extend the drying and subsequently the recoat time) | |
| Recoat time | 2 hrs |
| Flash Point | Not applicable |
| Packaging Sizes | 10L,4L,1L |
| Thinner and cleanup | Water(Upto 10% thinning when spraying depending on weather conditions) |
| Theoretical VOC(g/Ltr) | 45 |

Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface. Use **APCO BIOWash(SDS 9009)** as a moss and mould remover.
 Fill cracks and imperfections with a suitable filler and spot prime
 With a non-abrasive scourer, soaked in White Spirits, scrub the entire surface to be painted. Once the entire surface has been de-greased, wipe any excess off with a clean rag and allow the surface to dry.

Undercoat Requirements

Not applicable

Application and Process

Stir the contents thoroughly before and during use
 Apply one liberal coat then sand smooth before applying topcoats
 Apply by brush, roller or spray

For Best Results

- To ensure proper adhesion to any smooth surfaces, a non-abrasive scourer soaked in White Spirits must be used to clean the entire surface prior to application.
- Allow a minimum of 2 hours prior to applying a second coat and a minimum of 4 hours prior to sanding and applying any top coats.

Health and Safety

PRODUCT DATA SHEET

PDS No: 1006

- Please refer to Safety Data Sheet **(1005)** before use
- Use in well ventilated areas
- **First Aid:**
 - Eyes and Skin irritation – Wash with large amounts of fresh running water
 - If swallowed – drink 2-3 glasses of water and seek appropriate medical advice

Transport : Not Applicable
Class : Not Applicable
Hazchem : Not Applicable

Storage

Store in cool, well ventilated areas away from direct sunlight. Keep containers tightly sealed.

Spillage and Disposal

Use rags or sawdust to contain any spill and then dispose of through a commercial waste disposal organisation.

*Please refer to the updated versions of Safety data sheet(SDS) and Technical Data sheet (TDS) before using any **APCO** Product.*

KEEP OUT OF REACH OF CHILDREN

APCO Coatings (NZ) Limited

Ph. (09) 2733 041. Fax. (09) 2733 045. Physical Add. 14 Ron Driver Place, East Tamaki, Auckland 2013

The information and recommendations set down here in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd gives no guarantee to the completeness and accuracy thereof.

APCO Coatings (NZ) Ltd is not be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the Technical Data Sheet refers.