



APCOFILL

2-Pack EPOXY FILLER

PRODUCT DESCRIPTION

Apcofill is a 2 pack, high viscosity, thixotropic adhesive epoxy filler / jointing compound. When A and B are mixed it gives a strong, permanent, flexible filler and bond.

FEATURES

Apcofill has outstanding adhesion, even on damp surfaces. Water can be applied to the surface to assist smoothing and finishing, and will prevent surface tack. Cures well even around 3°C in damp conditions.

USES

For use in all Industrial and Marine filling applications including below water areas where adhesion and strength are paramount. Ideal for repairing all types of concrete & fiberglass surfaces on concrete floors and under Poolkote and Pitakote pool paint coatings.

MIXING

Ratio by volume: Equal parts A and B, 1 to 1

SEALING

If the surface is especially porous, then an Epoxy Sealer will be required prior to the application of Apcofill.

PREPARATION

All concrete surfaces must be cleaned/water-blasted and then acid etched.

NUMBER OF COATS 1 - 2 flushing coats will be required.

DRY TIME

Touch Dry: 4 - 10 hours, depending on film build and ambient conditions.
Recoat Time: Minimum 16 hours, depending on film build and ambient conditions.

COLOUR Beige

CLEAN UP Soap and water prior to curing.

Flammability & Transport Highly flammable, Dangerous Goods Class 3.2, Flash Point 180C. BASE- UN 1263, PG III, HARDENER- UN 2206 PG III

KEEP OUT OF REACH OF CHILDREN



09 2733041
0800 BUY APCO
14 Ron Driver Place
East Tamaki
Auckland