

## MPT earthtone Elastomeric Finish

### Description:

MPT Earthtone Elastomeric Finish is formulated on an adhesion promoted, flexible pure acrylic polymer that combines excellent adhesion, water and alkali resistance and exceptional weather resistance, with crack bridging capability up to 1mm. The low sheen finish will promote good soil resistance and a finish that is easy to clean. The high build properties of this coating enhances application on difficult to apply substrates and produces a very tough finish. A dry film thickness of 100 microns per coat can be achieved.

### Features and Benefits:

- Excellent adhesion and build over Limebuster, and other primed surfaces.
- Excellent flexibility, bridging surface cracks up to 1mm.
- Quick dry.
- High water and alkali resistance.
- Excellent weather resistance and low dirt pick-up.
- Can be self-textured by using special texture rollers.

### Limitations:

- Do not apply when ambient temperature is below 10°C. or surface temperature is above 45°C.
- Apply as supplied – do not thin

### Technical Data:

<b>Resin Type:</b>	Adhesion Promoted Pure Acrylic polymer
<b>Pigmentation:</b>	Titanium Dioxide and inert extenders
<b>Solvents:</b>	Water
<b>Colour:</b>	White and pastel tints
<b>Gloss Level:</b>	Low sheen
<b>Density:</b>	1.43 Kgs/ Litre
<b>Dry-Time:</b>	30 mins Touch, 4 hour between overcoat
<b>Coverage:</b>	4 – 6 M <sup>2</sup> per litre
<b>No. of coats:</b>	Two
<b>Packaging sizes:</b>	10 Litre
<b>Flash Point:</b>	None
<b>Thinner:</b>	Water

**Technical Data Sheet:**  
**Product No: MPT EW/10L**



**Surface Preparation:**

Remove all unsound paint, surface grease and oil, dirt etc. Treat mould affected areas with APCO Biowash Moss & Mould Remover.

**Application:**

Apply one to two coats of MPT Earthtone Elastomeric Finish to required dry film thickness, by Airless Spray, brush or roller. MPT Earthtone Elastomeric Finish can be textured by using Texture Rollers.

**For Best Results:**

- 1) Ensure correct dry film thickness is achieved.
- 2) Allow at least 4 hours before over-coating.
- 3) Do not apply in direct sunshine.

**Health and Safety:** (Please refer to Material Safety Data Sheet before using)

**MPT earthtone Elastomeric Finish** is essentially non-flammable and non-hazardous.

**KEEP OUT OF REACH OF CHILDREN**



0800 BUY APCO  
Ph. 09) 2733 041  
Fax. 09) 2733 045

PO Box 58849  
Botany  
Manukau 2163