

Acrylic Sealer Undercoat

Description

Ezicover Acrylic Sealer Undercoat is a premium quality, easy sanding, fast drying, general purpose, acrylic undercoat designed for use on a variety of interior surfaces. Suitable for new paper-faced plasterboard, mdf (custom wood) & interior timber.

Features and Benefits

- Easy application, easy sanding
- Excellent adhesion to properly prepared surfaces
- Excellent coverage/hiding power
- Excellent hold-out
- Ideal for new paper-faced plasterboard walls and ceilings
- Imparts even porosity to the surface
- Low splatter
- Low VOC
- Mould resistant

Limitations and Precautions

- Not recommended for wet areas.
- Some surfaces may require the use of an oil based sealer or primer. E.g. discoloured or very aged previously painted surfaces or aged unpainted paper-faced plasterboard. A test application should be done first to ensure proper adhesion.
- Do not apply when the surface temperature is below 10°C or above 35°C.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply if humidity is 85% or above.

Technical Data

Resin Type	Acrylic Emulsion
Colour	White
Gloss Level	na
Dry Times	Touch dry: 30 minutes Minimum Re-coat: 2 hours Cool temperatures, high film thickness or high humidity will require longer drying times.
Theoretical Coverage	8 - 10 m ² per litre
No. of coats	One.
Flash Point	None
Thinner	Water
Theoretical VOC	45 g/l

Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface.

Fill cracks and imperfections with a suitable filler and spot prime.

Previously painted surfaces should be sanded to remove loose or flaking paint and to reduce the previous film to a flat finish.

Application

Stir the contents thoroughly before and during use.

Apply one liberal coat then sand smooth before applying topcoats.

Apply by brush, roller or spray.

For Best Results

- The use of an 8 – 10mm nap roller is recommended.
- Allow a minimum of 2 hours prior to sanding and top-coating.
- If over-coating with a dark colour, then Ezicover Acrylic Sealer Undercoat should be tinted to assist coverage from the top coat.

Health and Safety (Please refer to Material Safety Data Sheet before using)

Ezicover Acrylic Sealer Undercoat is non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN

Product Number

EZIB101S

V 1.2 - 06.15

Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.