

Ultra Low Sheen Acrylic

Description

Ezicover Ultra Low Sheen Acrylic is a professional quality, extremely versatile, interior finish. Suitable for walls and ceilings in living areas.

Features and Benefits

- Easy application
- Excellent adhesion to primed and properly prepared painted surfaces
- Excellent coverage
- Ideal for wall and ceilings in living areas with high illumination
- Low splatter
- Low VOC
- Mould resistant
- Subtle sheen level which hides imperfections

Limitations and Precautions

- Not recommended for bathrooms, kitchens or laundries.
- Avoid cleaning the paint surface in the first 4 – 6 weeks.
- Do not apply when the surface temperature is below 10°C or above 35°C.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply if humidity is 85% or above.
- Being thermoplastic, the film is sensitive towards alcohol and aromatic hydrocarbons.
- Always test cleaning solutions to make sure they will not damage the paint surface.
- Some insect treatments contain chemicals that can soften and stain painted surfaces.

Technical Data

Resin Type	Acrylic Emulsion
Colour	White & tint bases
Gloss Level	<4 @ 60°
Dry Times	Touch dry: 30 minutes Minimum Re-coat: 2 hours Full cure: 7 days Cool temperatures, high film thickness or high humidity will require longer drying times.
Theoretical Coverage	10 - 12 m ² per litre
No. of coats	Two
Flash Point	None
Thinner	Water
Theoretical VOC	32 g/l

Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface.

Fill cracks and imperfections with a suitable filler and spot prime.

Previously painted surfaces should be sanded to remove loose or flaking paint and to reduce the previous film to a flat finish.

Undercoat Requirements

New Paper-faced Plasterboard:

Ezicover Acrylic Sealer Undercoat or Ezicover Smooth-coat.

New Woodwork, Plywood, Hardboard:

Ezicover Acrylic Primer Undercoat or Ezicover Alkyd Primer Undercoat.

Aged Plaster and Paper-faced Plasterboard, discoloured or very aged previous paint:

Ezicover Pigmented Sealer.

Application

Stir the contents thoroughly before and during use.

Apply two liberal coats of Ezicover Ultra Low Sheen Acrylic with light sanding between coats.

Apply by brush, roller or spray.

For Best Results

- The use of an 8 – 10mm nap roller is recommended.
- Allow a minimum of 2 hours prior to sanding and recoating.
- For best results, apply one coat of Ezicover Smooth-coat by spray application, then one coat of Ezicover Acrylic Sealer Undercoat.
- When painting over medium to dark colours, a tinted undercoat must be used for superior coverage.

Health and Safety (Please refer to Material Safety Data Sheet before using)

Ezicover Ultra Low Sheen Acrylic is non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN

Product Numbers

EZIT100	White
EZIT105	Mid Tone base
EZIT103	Ultra Deep base
EZIT104	Extra Bright base

V 1.3 - 06.15

Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.