

**All 'n One Primer**

**Description**

Ezicover All 'n One Primer is a high performance, water-based preparation product. It has outstanding hiding, filling and sanding properties. Specifically formulated as a smooth surface sealer.

**Features and Benefits**

- Excellent adhesion to properly prepared smooth surfaces like glossy alkyds and varnishes
- Exceptional coverage/hiding power
- Low VOC
- Mould resistant
- Suitable for interior and exterior use
- When used as an undercoat, Ezicover All 'n One provides a smooth, even surface for topcoats to achieve maximum coverage and gloss level.

**Limitations and Precautions**

- Not recommended for fibrous plaster or very porous surfaces.
- Full adhesion and hardness will take a minimum of 7 days.
- The surface must be de-greased prior to application.
- Do not apply to timber that is showing signs of deterioration.
- Do not apply when the surface temperature is below 10°C or above 35°C.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply if humidity is 85% or above.

**Technical Data**

<b>Resin Type</b>	100% Acrylic Emulsion
<b>Colour</b>	White
<b>Gloss Level</b>	na
<b>Dry Times</b>	Touch dry: 30 minutes Minimum Re-coat: 2 hours Sand and Top-coat: 4 hours Full cure: 7 days Cool temperatures, high film thickness or high humidity will require longer drying times.
<b>Theoretical Coverage</b>	10 - 12 m <sup>2</sup> per litre
<b>No. of coats</b>	One (two for stained surfaces)
<b>Flash Point</b>	None
<b>Thinner</b>	Water
<b>Theoretical VOC</b>	45 g/l

### Surface Preparation

Remove all dirt, dust, grease, mould or any other form of contamination from the surface.

Remove any loose or flaking paint.

Fill cracks and imperfections with a suitable filler and spot prime.

With a non-abrasive scourer, soaked in White Spirits, scrub the entire surface to be painted. Once the entire surface has been de-greased, wipe any excess off with a clean rag and allow the surface to dry.

### Application

Stir the contents thoroughly before and during use.

Apply one liberal coat.

Apply by brush, roller or spray.

### For Best Results

- To ensure proper adhesion to any smooth surfaces, a non-abrasive scourer soaked in White Spirits must be used to clean the entire surface prior to application.
- Allow a minimum of 2 hours prior to applying a second coat and a minimum of 4 hours prior to sanding and applying any top coats.
- The use of good quality brushes and rollers is recommended.

**Health and Safety** (Please refer to Material Safety Data Sheet before using)

**Ezicover All 'n One Primer** is non-flammable and non-hazardous.

**KEEP OUT OF REACH OF CHILDREN**

#### Product Number

EZIB101P

V 1.2 - 06.15

Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.