

**Technical Data Sheet:**  
**Product No: EZIB301P**

## **APCO EZI-COVER**

### **Alkyd Primer Undercoat**

#### **Description:**

A professional high quality oil-based primer undercoat suitable for preparing all timber surfaces. With excellent opacity and film build, Ezicover Alkyd Primer Undercoat has deep penetrating and sealing properties. Easy to sand, it provides excellent intercoat adhesion.

#### **Features and Benefits:**

Ideal for use on wooden doors and windows, this product also may be used as an undercoat over previously primed timber. Also suitable for primed metal surfaces, plywood, paper faced wallboard and hardboard.

This primer undercoat may be tinted to desired pastel strength for facilitating changes to contrasting colours.

For interior and exterior use.

#### **Limitations:**

**Do not** apply when ambient temperature is below 10°C or surface temperature is above 40°C.

#### **Technical Data:**

<b>Resin Type:</b>	Alkyd resin
<b>Solvents:</b>	White Spirit
<b>Colour:</b>	White
<b>60° Gloss:</b>	N/A
<b>Density:</b>	1.40 Kgs/ Litre
<b>Dry-Time:</b>	4 hr touch dry, 16 hr overcoat
<b>Coverage:</b>	10 – 14 m <sup>2</sup> per litre
<b>Packaging sizes:</b>	4 and 10 litre
<b>Flash Point:</b>	<b>Flammable</b>
<b>Thinner:</b>	Thinner 600 or Mineral Turps



BRILLIANT PAINTS • BRILLIANT COLOURS

### **Surface Preparation:**

Remove all dirt, dust, grease and other contaminants. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill cracks and imperfections with a suitable filler and spot prime. Then apply a full coat of primer and sand lightly using 220-grit sandpaper. All previously painted surfaces may be sanded with 180-grit sandpaper to remove all flaking paint and to reduce previous film to a flat finish.

### **Application:**

Stir contents thoroughly before and occasionally during use. Apply by brush, roller or airless spray uniformly, after proper surface preparation. Apply single, uniform coat. Sand lightly using 220-grit sandpaper to a smooth finish, even finish. Dust off. Follow with two coats of finish.

**Health and Safety:** (Please refer to Material Safety Data Sheet before using)

**Ezicover Alkyd Primer Undercoat** is essentially **flammable – keep away from naked flame, DG Class 3.2, UN No. 1263, P.G. III**, but non-toxic. Does not contain any added toxic heavy metals such as lead, mercury etc. Provide plenty of ventilation and avoid breathing vapours.

**KEEP OUT OF REACH OF CHILDREN**



BRILLIANT PAINTS, BRILLIANT COLOURS

09 2733041

0800 BUY APCO

14 Ron Driver Place

East Tamaki

Auckland