

# SAFETY DATA SHEET

SDS NO: 9041



## 1. IDENTIFICATION OF THE PRODUCT AND COMPANY

### Product Details:

**Product Code** 58190 (58190/A Base:58190/B Hardener)  
**Product Name** 2 Pack WB Epoxy Clear Sealer  
2K water based gloss epoxy sealer  
**Description:** 2 Pack Waterborne Epoxy Clear Sealer is a waterborne, two pack clear epoxy sealer for concrete. Used for sealing concrete and plaster prior to over coating with epoxy finishes such as a hi build epoxy or water based epoxy coatings.

### Recommended Use

**UN No:** Not Regulated for Transport of Dangerous Goods  
**HAZCHEM:** Not applicable

### Supplier Details:

**Company** APCO COATINGS (NZ) LIMITED  
**Address** 14 Ron Driver Place, East Tamaki, Auckland 2163, New Zealand  
**Telephone** 09 273 3041  
**Fax** 09 273 3045  
**E Mail** [contact@apconz.co.nz](mailto:contact@apconz.co.nz)  
**Web** [www.apcocoatings.co.nz](http://www.apcocoatings.co.nz)

### Emergency Telephone Numbers:

**NZ POISON** 0800 POISON (0800 764 766)  
**CHEMWATCH** 0800 CHEMCALL (0800 243 622)  
**NZ Emergency Services** 111

## 2. HAZARD IDENTIFICATION

### Hazard Classification of the mixture:

#### HSNO Classification:

Classified as hazardous according to HSNO New Zealand 2008 criteria.

#### Hazchem Category:

Not Determined

#### GHS Classification & Legend:

Information extracted from the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) and the New Zealand HSNO Act equivalent.

#### Determined By Chemwatch us-Inf: No information at hand

#### HSNO Classification:

6.3A Irritating to the skin.  
6.4A Irritating to the eye.  
6.5B Contact sensitiser.  
8.3A Corrosive to ocular tissue.  
9.1A Very ecotoxic in the aquatic environment.

# SAFETY DATA SHEET



SDS NO: 9041

## Visible Identification:

HSNO  
Label:



**Danger Keep out of the reach of Children.**

## Hazard Statement:

As of March 2009, the relevant New Zealand regulations under the Hazardous Substances and New Organisms Act 1996 do not specify the exact wording required for hazard statements. The following hazards recognised by the GHS apply to this product with the severity dependant on the exposure levels:

## Physical Hazard(s)

Not applicable

## Health Hazard(s)

### HSNO Classes:

- 6.3A: Irritating to the skin.
- 6.4A: Irritating to the eye.
- 6.5B: Contact sensitiser.
- 8.3A: Corrosive to ocular tissue.
- 9.1A: Very ecotoxic in the aquatic environment.

### Hazard Statements:

- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H361: Suspected of damaging fertility or the unborn child.
- H400: Very toxic to aquatic
- H410: Very toxic to aquatic life with long lasting effects.

### Prevention:

- P103: Read label before use. P264: Wash hands thoroughly after handling.
- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P264: Wash skin thoroughly after handling.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P280a: Wear protective gloves and eye/face protection.

# SAFETY DATA SHEET



SDS NO: 9041

## Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTRE/doctor

P308 + P313 - IF exposed or concerned: Get medical advice/ attention.

P337 + P313 - If eye irritation persists: Get medical advice/ attention.

P302: IF ON SKIN: Wash with plenty of soap and water. Specific treatment: Rinse cautiously with water for 10 mins. If eye irritation persist: Remove contact lenses, if present and easy to do. Continue rinsing. P332: If skin irritation occurs. Get medical advice/attention. Take off contaminated clothing and wash before re-use.

## Storage:

P405 - Store locked up.

Keep container tightly closed. Store in well ventilated.

## Disposal:

P501 - Dispose of contents/ container to an approved waste disposal plant.

**Dispose of contents/container in accordance with local/regional/national/international regulations. Do not reuse the container for any other purpose. Dispose of in accordance with applicable laws and regulations.**

## Environmental Hazard(s)

H400: Very toxic to aquatic

H410: Very toxic to aquatic life with long lasting effects.

## 3. COMPOSITION / INFORMATION OF INGREDIENTS

Components	CAS Number	Proportion
Water	7732-18-5	15-35%
Epoxy acrylates		100%
Decanedioic acid, compds. w/1,3- benzenedimethanamine-bis α-deta glyc ph et rx prod- epic-form-propylene-oxide- teta pol	260549-92-6	30-60%
Additives		<1%

# SAFETY DATA SHEET

SDS NO: 9041



## 4. FIRST AID MEASURES

### First Aid Measures:

<b>Eye Contact</b>	Immediately flush eyes with plenty of water and remove contacts where possible, ensure that the eyes are flushed for 15 minutes with the eyes wide open. <b>If the person still feels unwell or irritation persists then take those exposed to the doctor.</b>
<b>Skin Contact</b>	Immediately wash affected area on the skin with soap and water for 20 minutes and ensure clothing and footwear is removed immediately if possible. <b>Seek medical advice if large areas of skin are involved or irritation persists.</b>
<b>Inhalation</b>	Exposure to high vapor concentrations may cause eye and respiratory tract irritation, headaches, dizziness, nausea, uncoordination, drowsiness, and loss of consciousness. Immediately remove the person to a fresh air environment away from harm. <b>If their breathing is difficult give them oxygen and or give cardiopulmonary Resuscitation if breathing has stopped. If breathing difficulties persist take them to the doctor immediately.</b>
<b>Ingestion (Swallowed)</b>	If swallowed, do NOT induce vomiting. Rinse mouth. Get medical attention. If spontaneous vomiting occurs, hold patients head below hips to avoid possible aspiration of vomitus into lungs. <b>Never give anything by mouth to an unconscious person. seek medical advice immediately</b>

### Advice to Doctors:

Treat according to symptoms. Repeated or prolonged exposure by inhalation to mixed hydrocarbons may result in dizziness, weakness, irritability, lack of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys.

### Emergency overview:

For advice in an emergency, contact the Poisons Information Centre or **if breathing difficulties are acute take those affected to the doctor or A&E immediately.**

## 5. FIRE FIGHTING MEASURES

### Hazards from combustion products:

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

### Extinguishing Media:

Water fog, water spray, dry chemical, foam, carbon dioxide

# SAFETY DATA SHEET

SDS NO: 9041



## Precautions in connection with fire:

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and water courses.

## 6. ACCIDENTAL RELEASE MEASURES

Clear area of all unprotected personnel and notify the local authorities where contamination of sewers or waterways has occurred advise emergency services. Wear full protective equipment and respirators where mist or vapors exist in unknown quantities.

- If inhalation risk exists, use local exhaust ventilation.
- Vapours are heavier than air.
- Place a barrier between the workers and the hazard.

## Large amounts:

Do not allow the product to enter drains, sewers or waterways. Dike and soak up with inert material such as dry sand, and vermiculite. Remove liquid to containers for recovery and separate inert material to containers away from the recovered liquid. Ensure the clean up of this material is in accordance with local authority bylaws.

## Disposal and cleaning of equipment:

Dispose of waste generated from the clean up of this material in accordance with local authority bylaws. All cleaning aides and equipment must be cleaned without letting the waste run into waterways, drains and sewers, tools used to clean up must be non sparking.

## Methods and materials for containment and clean up:

Dispose of waste generated from the clean up of this material in accordance with local authority bylaws. All cleaning aides and equipment must be non sparking and cleaned in accordance with national, regional and local authority bylaws

# SAFETY DATA SHEET



SDS NO: 9041

## 7. HANDLING AND STORAGE

Avoid contact with eyes and skin. Wear overalls, impervious gloves and safety glasses.

### Precautions for safe handling:

- Read product label before use.
- Keep container closed and Handle containers with care.
- Open slowly to control possible pressure release.
- Do not use plastic buckets.
- Use outdoors or in well-ventilated area.
- Wear personal protective equipment.
- Wash hands with soap and water after handling.
- Wash protective clothing separate to household laundry.

### Conditions for safe storage:

- Keep out of reach of children.
- Store in cool, dry, well ventilated place and out of direct sunlight  
Keep container tightly closed.
- Store at room temperature-do not freeze
- Keep away from heat and sources of ignition.
- Segregate from food and feed sources
- Avoid release to the environment.
- Do Not contaminate drinking water, through storage or disposal.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Health Exposure Standards: Not available in NZ WES

Source	Material Name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	xxxxx	xxxx	xxxx	xxx	xxxxx

Exposure Controls: wear the appropriate PPE

Personal Protection



# SAFETY DATA SHEET

SDS NO: 9041



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Colourless Clear, viscous liquid
<b>Odour</b>	Fishy
<b>Solubility in water (g/l)</b>	Dispersible
<b>Flash Point (°C)</b>	Not available
<b>Boiling Point (°C)</b>	Not available
<b>Melting point / freezing point (°C)</b>	Not available
<b>Vapour Pressure (Pa) at 20degC</b>	Not available
<b>Specific Gravity (Kg/Ltr)</b>	1.05 - 1.15
<b>% of Volatile (wt)</b>	50
<b>pH</b>	n/a
<b>VOC (g/l)</b>	< 10

## 10. STABILITY AND REACTIVITY

- **Chemical Stability:** Stable under normal conditions of storage and handling
- **Hazardous reactions:** this product has no identifiable reactive properties
- **Conditions to avoid:** Store in a well vented area

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects:

#### Ingestion:

may cause vomiting and aspiration into lungs and cause chemical pneumonitis or pulmonary edema. If swallowed, symptoms may include headaches, nausea, dizziness and tracheal burning.

#### Eye Contact:

This product may be irritating to the eyes resulting in tearing and redness and can damage eye tissue.

#### Skin Contact:

This product can be corrosive to the skin. Prolonged or repeated exposure may defat skin leading to drying, cracking and serious burns to the skin.

#### Inhalation:

Vapours may cause discomfort or irritation to the upper respiratory tract. Symptoms of over-exposure may be coughing, choking, wheezing, difficulty in breathing, drowsiness and dizziness.

#### Chronic Effects:

Repeated or prolonged exposure by inhalation to mixed hydrocarbons may result in dizziness, weakness, irritability, lack of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys. Auditory system effects may include temporary hearing loss and/or ringing in the ears.

# SAFETY DATA SHEET



SDS NO: 9041

## Toxicity:

This product is suspected of damaging fertility or the unborn child. In addition it may cause damage to organs through prolonged or repeated exposure.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity:

Do not discharge product to sewer, drains or waterways.

### Aquatic toxicity:

This product has been classified as being toxic to aquatic life with long-term effects.

### Persistence/degradability:

Not expected to be persistent or bioaccumulative. However contains components that may not be readily biodegradable. Degrades rapidly in air.

### Mobility:

Product is miscible with water and is mobile in soil and may contaminate groundwater.

### Large amounts:

Do not allow the product to enter drains,sewers or waterways. Dike and soak up with inert material such as dry sand, vermiculite. Remove liquid to containers for recovery and separate inert material to containers using non spark equipment and away from the recovered liquid. Ensure the clean up of this material in accordance with local authority bylaws.

### Disposal and cleaning of equipment:

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain product vapours. Allow container to dry before disposal. Do not use container for storing other products. **Do Not** let clean up residue enter storm water, sewers or waterways and clean up in accordance with national, regional and local authority regulations.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods:

Dispose of product through waste management facility for solvent recovery or disposal, e.g. by incineration. Always follow the waste treatment procedures of national, regional and local authority regulations. Ensure that authorised contractors and or approved handlers dispose of the product and its containers.

## 14. TRANSPORT INFORMATION

### Land Transport (UN):

**UN Number:** Not Regulated for Transport of Dangerous Goods

### Air Transport (ICAO-IATA / DGR):

**UN Number** Not Regulated for Transport of Dangerous Goods



# SAFETY DATA SHEET



SDS NO: 9041

## Sea Transport (IMDG-Code / GGV See):

UN Number Not Regulated for Transport of Dangerous Goods

## 15. REGULATORY INFORMATION

### Reference material:

- EPA January 2012 EPA0094, Labelling of hazardous substance.
- EPA January 2012 EPA0125, Correlation between GHS and New Zealand HSNO Hazard Classes and Categories.
- HSNO act 1996 and Dangerous Goods 2005 and all subsequent amendments.
- Workplace Exposure Standards for Airborne contaminants (ISBN 978-1-74361-055-8) Online pdf
- Health and Safety at Work Act 2015 and the Health and Safety at work Regulations 2016
- Sea Maritime Rule 24A and IMDG Dangerous Goods NZ and International
- Air Civil Aviation Rule Part 92, ICAO Dangerous Goods NZ and International
- Rail Land Transport Rule 45001/1 & NZS 5433

## 16. OTHER INFORMATION

### Definitions and abbreviations:

<b>CAS No</b>	Chemical Abstract Number
<b>ERMA</b>	Environmental Risk Management Authority
<b>PC-TWA</b>	Permissible Concentration – Time Weighted Average
<b>PC-STEL</b>	Permissible Concentration – Short Term Exposure Limit
<b>HSNO</b>	Hazardous Substance and New Organisms
<b>WES</b>	Workplace Exposure Standard
<b>TEEL</b>	Temporary Emergency Exposure Limit
<b>IDLH</b>	Immediately Dangerous to Life or Health Concentrations
<b>OSF</b>	Odour Safety Factor
<b>NOAEL</b>	No Observed Adverse Effect Level
<b>LOAEL</b>	Lowest Observed Adverse Effect Level
<b>TLV</b>	Threshold Limit Value
<b>LOD</b>	Limit Of Detection
<b>OTV</b>	Odour Threshold Value
<b>BCF</b>	BioConcentration Factors
<b>BEI</b>	Biological Exposure Index
<b>STEL</b>	Short Term Exposure Limit

### Note:

The information in this SDS was obtained from sources, which we believe were reliable at the time of creating this SDS. However, the information is provided without any presentation or warranty, expressed or implied, regarding its accuracy. The information and recommendations herein, are to the best of our knowledge, true and accurate. No Warranty, express or implied is made or intended.