

RAPID STRIP

PAINT REMOVER

Product Description

It is a non-caustic and effective paint removing gel suitable for easy removal of all enamels, varnishes and lacquers. It's unique gel formulation helps to deposit the material evenly on vertical surfaces for easy removal of coatings.

Areas of Application

To remove old coatings from timber, metal and concrete surfaces. It is effective for 2 Pack paint as well.

Technical Data

Colour range	: N/A
Gloss Level at 60° head	: N/A
Solvent Resistance	: N/A
Toxicity	: Contains 87% w/v Methylene Chloride.
Solvent for Thinning & Clean-up	: N/A
Theoretical Coverage	: 5sqm p/ltr Practical coverage depends on deposition and surface porosity.
Drying Time(at 25°C & RH 60%)	: N/A
Packs available	: 4L, 1L, 500ml, 250ml

Method of Application

Most suitable method for application is by using a brush of required size. An old paintbrush is ideal.

Surface Preparation

Wipe the surface clean. Loosely adhered paint shall be removed fully by mechanical means.

Application

Stir the content thoroughly. Apply uniformly by brush. Ensure that all the areas are covered with Paint stripper. Allow the paint stripper to remain for 10 minutes so as to soften the old paint. After 10 minutes, with the help of suitable scrapper remove the paint gently. It is recommended to wear safety gloves while using this product.

Repeat the above procedure if there is still some paint left on the surface. Wash the surface thoroughly.

Flammability & Transport Information

Highly flammable, Dangerous goods clause 3.2 Flash point less than 10 degree Celsius UN1912 PG II

A horizontal banner with a background of colorful paint splatters in shades of green, blue, red, purple, and yellow. The text 'BRILLIANT PAINTS • BRILLIANT COLOURS' is overlaid in white, bold, sans-serif font.

BRILLIANT PAINTS • BRILLIANT COLOURS

Safety & Precautions:

Avoid contact with skin.
Keep away from heat and open flame.
Keep out of reach of children.
Refer to the material safety data sheet before using the product.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

APCO Coatings NZ Ltd

PO Box 58849 Botany 2163 Greenmount

Ph 09 2733 041

Fax 09 2733 045