



# TIMBERCARE

## Acrylic Low Sheen

### **Product Description**

This is a 100% premium Acrylic low sheen finish, suited for all types of timber surfaces. It's superior flow and unique hardness properties help to provide smooth and hardwearing finish. The product can also be used without primer for protection of wood from UV degradation. Timbercare 100% Acrylic wood finish is available in exciting contemporary and traditional colours.

### **Areas of Application**

Dressed or rough sawn bare timber, plywood, hardboard and custom wood surfaces. This product can also be applied on suitably primed concrete and metal surfaces.

*For interior and exterior use.*

### **Technical Data**

Colour Range	: Black, White, Karaka, Redwood, Brunswick Green & Permanent Green
Gloss Level at 60° head	: 10-12 %
Solvent Resistance aromatic hydrocarbons.	: Being thermoplastic, film sensitive towards alcohol and
Toxicity	: Dry film is non toxic and lead free.
Thinning & Clean Up	: Water. Though this product is designed for undiluted application, it may be diluted up to 10% if necessary.
Coverage	: 12 sq. m. / litre per coat. Practical coverage may depend on surface profile, method of application and losses.
Drying Time (at 25° C & RH 60%)	: Touch dry: 30 minutes Recoat : 4 hours Cooler temperature, higher film thickness or higher humidity conditions will require longer drying times.
Packs available	: 10 L