

ezi•cover Tag Out

Product Description

Ezicover Tag Out is a 100% acrylic low sheen finish, specifically formulated for painting out graffiti. This product can be used without a primer on a variety of exterior surfaces.

Features & Benefits

- Suitable for all types of timber
- Can also be used on concrete, masonry & fibre cement.
- Excellent coverage/hiding
- Easy to apply
- Fast drying
- No primer required

Technical Data

Colour Range	Black, Brown, Green & Grey
Gloss Level at 60° head	3 - 6%
Solvent Resistance	Being thermoplastic, the film is sensitive to alcohol and aromatic hydrocarbons.
Toxicity	Dry film is non toxic and lead free.
Thinning & Clean Up	Water. Though this product is designed for undiluted application, it may be diluted up to 20% if necessary.
Coverage	8 - 10 sq. m. / litre per coat. Practical coverage may depend on surface profile, method of application and losses.
Drying Time (at 25° C & RH 60%)	Touch dry: 30 minutes. Recoat: 2 hours Cooler temperature, higher film thickness or higher humidity conditions will require longer drying times.
Packs available	10 L
VOC	28 g/l



Method of Application

Brush, Roller or Spray. Please use the method best suited to your requirement and skill. The quality of finish may depend on type of brush or roller sleeve used. If in doubt, please seek the professional advice from your local suppliers regarding the most suitable brush or roller sleeve for the job.

Surface Preparation

Remove all moss, mould, dirt, dust & loose flaking paint. Clean the entire area to be painted. Fill surface imperfections like nail holes, cracks etc by suitable exterior grade filler. Sand smooth with 220-mesh sandpaper and dust off.

Application

Stir the contents thoroughly before and during use. On tannin rich timbers, use one coat of Apcolite Acrylic Primer. Thin the first coat by 10 – 20% with water.

For Best Results:

- 1) Apply 2 - 3 coats in coastal areas
- 2) Do not paint in direct sunlight
- 3) Thin the first coat up to 20% with water – especially on aged or dry timber & porous substrates.

Flammability & Transport Information

Non-flammable

Safety & Precautions

Do not apply when surface temperature is below 10⁰ C

Provide adequate ventilation during use.

Keep out of reach of children.

Check cross cut adhesion of old paint before repainting.

In normal condition, a week's curing is required to develop full hardness & resistance.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.



0800 BUY APCO
Ph. 09) 2733 041
Fax. 09) 2733 045

PO Box 58849
Botany
Manukau 2163